

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,090,408 B2
APPLICATION NO. : 10/816323
DATED : August 15, 2006
INVENTOR(S) : Brief et al.

Page 1 of 4

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

| | |
|-------------------|--|
| Column 1, Line 14 | Delete: "directed to a hew" Insert: --directed to a new-- |
| Column 2, Line 28 | Delete: "base member's end walls" Insert: --base member's endwalls-- |
| Column 2, Line 43 | Delete: "the inverted-L shaped" Insert: --the inverted L-shaped-- |
| Column 2, Line 50 | Delete: "includes a slotted end" Insert: --includes a slotted end- -- |
| Column 2, Line 54 | Delete: "slotted end wall member" Insert: --slotted endwall member-- |
| Column 2, Line 55 | Delete: "allows the end wall member" Insert: --allows the endwall member-- |
| Column 2, Line 56 | Delete: "to the end wall" Insert: --to the endwall-- |
| Column 3, Line 2 | Delete: "alignment pis assembly is located." Insert: --alignment pin assembly is located.-- |
| Column 3, Line 8 | Delete: "In this position the" Insert: --In this position, the-- |
| Column 3, Line 13 | Delete: "then 'snap'locks the lid" Insert: --then 'snap'-locks the lid-- |
| Column 3, Line 14 | Delete: "has cleared the Lip." Insert: --has cleared the lip.-- |
| Column 4, Line 40 | Delete: "End wall 108" Insert: --Endwall 108-- |
| Column 4, Line 48 | Delete: "adjacent to the end" Insert: --adjacent to the end- -- |

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,090,408 B2
APPLICATION NO. : 10/816323
DATED : August 15, 2006
INVENTOR(S) : Brief et al.

Page 2 of 4

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

| | |
|-------------------|---|
| Column 4, Line 60 | Delete: "adjoined by an slot 181" Insert: --adjoined by a slot 181-- |
| Column 4, Line 64 | Delete: "slot cooperate with. cavity 161" Insert: --slot cooperate with cavity 161-- |
| Column 5, Line 22 | Delete: "through apertures. 131" Insert: --through apertures 131-- |
| Column 5, Line 26 | Delete: "clear the inverted-L shaped" Insert: --clear the inverter L-shaped-- |
| Column 5, Line 35 | Delete: "slotted end wall or" Insert: --slotted endwall or-- |
| Column 5, Line 37 | Delete: "The slotted end wall member" Insert: --The slotted endwall member-- |
| Column 5, Line 41 | Delete: "slotted end wall member 200 has" Insert: --slotted endwall member 200 has-- |
| Column 5, Line 42 | Delete: "that allows the end wall member" Insert: --that allows the endwall member-- |
| Column 5, Line 43 | Delete: "adjacent to the end wall 108" Insert: --adjacent to the endwall 108-- |
| Column 5, Line 60 | Delete: "pis assembly is located." Insert: --pin assembly is located.-- |
| Column 6, Line 4 | Delete: "end wall 110," Insert: --endwall 110,-- |
| Column 6, Line 6 | Delete: "up and aver the lip 159" Insert: --up and over the lip 159-- |
| Column 6, Line 7 | Delete: "the lid in portion," Insert: --the lid in position,-- |

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,090,408 B2
APPLICATION NO. : 10/816323
DATED : August 15, 2006
INVENTOR(S) : Brief et al.

Page 3 of 4

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

| | |
|-------------------|---|
| Column 6, Line 48 | Delete: "configured to placed upon" Insert: --configured to be placed upon-- |
| Column 6, Line 65 | Delete: "said base member so that" Insert: --said base member, so that-- |
| Column 7, Line 11 | Delete: "4. TM module according to claim 2," Insert" --4. The module according to claim 2,-- |
| Column 7, Line 19 | Delete: "and wherein & bottom" Insert" --and wherein a bottom-- |
| Column 7, Line 20 | Delete: "member a leveled surface" Insert" --member has a bevelled surface-- |
| Column 7, Line 21 | Delete: "lip adjacent to the end wall" Insert" --lip adjacent to the endwall-- |
| Column 7, Line 30 | Delete: "prising the steps of;" Insert" --prising the steps of:-- |
| Column 7, Line 43 | Delete: "the two NIT ferrules" Insert" --the two MT ferrules-- |
| Column 7, Line 53 | Delete: "(f) locating sad cover" Insert" --(f) locating said cover-- |
| Column 8, Line 1 | Delete: "and then 'snap'locks the lid in" Insert: --and then 'snap'-locks the lid in-- |
| Column 8, Line 19 | Delete: "pair of planar side walls that" Insert: --pair of planar sidewalls that-- |

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,090,408 B2
APPLICATION NO. : 10/816323
DATED : August 15, 2006
INVENTOR(S) : Brief et al.

Page 4 of 4

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 8, Line 55 Delete: "end wall of the base member"
 Insert: --endwall of the base member--

Signed and Sealed this

Twenty-first Day of November, 2006

A handwritten signature in black ink, appearing to read "Jon W. Dudas". The signature is stylized with a large, looped initial "J" and a cursive "Dudas".

JON W. DUDAS
Director of the United States Patent and Trademark Office